












# HID® Prox I25 kHz Proximity – Credentials

HID Prox

	 ProxCard® II	 ISOProx® II	 DuoProx® II	 Smart ISOProx II™	 Smart DuoProx® II	 iCLASS® Prox	 MIFARE®/Prox	 ProxCard® Plus	 ProxKey® III	 MicroProx® Tag	 ProxPass® II
<b>Base Part Number</b>	1326	1386	1336	1597	1598	202X/212X; 203X/213X	1431	169	1346	1391	1351
<b>Read Range: *</b>											
<b>ProxPoint® Plus</b>	Up to 3.0" (7.5 cm)	Up to 2.5" (6.5 cm)						Up to 1.0" (2.5 cm)	Up to 1.5" (4.0 cm)	Up to 2.0" (5.0 cm)	N/A
<b>MiniProx®</b>	Up to 5.5" (14.0 cm)	Up to 5.0" (12.5 cm)						Up to 2.0" (5.0 cm)		Up to 2.5" (6.5 cm)	N/A
<b>Thinline® II</b>	Up to 5.5" (14.0 cm)	Up to 5.0" (12.5 cm)						Up to 1.5" (4.0 cm)	Up to 2.0" (5.0 cm)	Up to 3.0" (7.5 cm)	N/A
<b>ProxPro®</b>	Up to 8.0" (20.5 cm)	Up to 7.0" (18.0 cm)						Up to 3.0" (7.5 cm)		Up to 4.0" (10.0 cm)	N/A
<b>ProxPro® II</b>	Up to 9.0" (23.0 cm)	Up to 8.0" (20.0 cm)						Up to 4.0" (10.2 cm)		Up to 4.5" (11.5 cm)	N/A
<b>MaxiProx®</b>	Up to 29.0" (74.0 cm)	Up to 20.0" (51.0 cm)						Up to 13.0" (33.0 cm)	Up to 12.0" (28.0 cm)	Up to 15.0" (38.0 cm)	Up to 6.0" (1.8 m)
<b>EntryProx™</b>	Up to 3.0" (7.5 cm)	Up to 2.5" (6.5 cm)						Up to 1.0" (2.5 cm)	Up to 1.5" (4.0 cm)	Up to 2.0" (5.0 cm)	N/A
<b>Prox80™</b>	Up to 5.5" (14.0 cm)	Up to 5.0" (12.5 cm)	Up to 2.5" (6.0 cm)		Up to 5.0" (12.5 cm)		Up to 1.5" (3.5 cm)	Up to 2.0" (5.0 cm)	Up to 2.5" (6.0 cm)	N/A	
<b>Memory Size/ Application Area</b>	N/A				2k bits with two application areas; 16k bits with two application areas, 16k bits with 16 application areas; 32k bits (16k/2+16k/1), 32k bits (16k/16+16k/1)		MIFARE 1K: 1K Byte (8k bits) in 16 64-byte Sectors  MIFARE 4K: 4K Byte (32k bits) in 40 Sectors: 32 sectors of 64 bytes, 8 sectors of 256 bytes.			N/A	
<b>HID Proximity 125 kHz</b>	Yes										
<b>Contact Smart Chip Module Embeddable</b>	No		Yes**		Optional**		No				
<b>Wiegand Strip</b>	No						Yes	No			
<b>Magnetic Stripe</b>	No	Yes	No	Yes	Optional						
<b>Printable ***</b>	Yes								No		
<b>Standard HID Artwork</b>	Optional								Yes	Yes	N/A
<b>Slot Punch</b>	Vertical (standard)	Horizontal or Vertical Optional		Vertical Optional				Horizontal or Vertical Optional	Key Ring Hole	No	
<b>Visual Security Options</b>	N/A	Yes								N/A	
<b>Additional Security Options</b>	Corporate 1000										
<b>Warranty</b>	Lifetime										One Year

\* Dependant upon installation conditions.

\*\* Contact smart chip module not included. Ask about HID's SMARTS Program for off-the-shelf contact smart chip embedded cards.

\*\*\* Some types of printing processes can take these credentials out of ISO compliance for thickness. Consult factory for more information.